

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan


“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 6441-1 (1972): Methods of test for autoclaved cellular concrete products, Part I: Determination of unit weight or bulk density and moisture content [CED 53: Cement Matrix Products]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

**METHODS OF TEST FOR AUTOCLAVED
CELLULAR CONCRETE PRODUCTS**

**PART I DETERMINATION OF UNIT WEIGHT OR BULK
DENSITY AND MOISTURE CONTENT**

(Fourth Reprint NOVEMBER 1994)

UDC 666.973.6:531.75

© Copyright 1972

BUREAU OF INDIAN STANDARDS

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

METHODS OF TEST FOR AUTOCLAVED CELLULAR CONCRETE PRODUCTS

PART 1 DETERMINATION OF UNIT WEIGHT OR BULK DENSITY AND MOISTURE CONTENT

Cement and Concrete Sectional Committee, BDC 2

Chairman

DR H. C. VISVESVARAYA

Representing

Cement Research Institute of India, New Delhi

Members

DR A. S. BHADURI

National Test House, Calcutta

SRI E. K. RAMACHANDRAN (Alternate)

SRI A. K. CHATTERJI

Central Building Research Institute (CSIR),
Roorkee

DR S. S. REHSI (Alternate)

DIRECTOR

Central Road Research Institute (CSIR),
New Delhi

DR R. K. GHOSH (Alternate)

DIRECTOR (CSMRS)

Central Water & Power Commission, New Delhi

DEPUTY DIRECTOR (CSMRS) (Alternate)

SRI K. C. GHOSAL

Alokudyog Services Ltd, New Delhi

SRI A. K. BISWAS (Alternate)

DR R. K. GHOSH

Indian Roads Congress, New Delhi

DR R. R. HATTIANGADI

Associated Cement Companies Ltd, Bombay

SRI P. J. JAGUS (Alternate)

JOINT DIRECTOR, STANDARDS
(B & S)

Research, Designs & Standards Organization
Lucknow

DEPUTY DIRECTOR,
STANDARDS (B & S) (Alternate)

SRI S. B. JOSHI

S. B. Joshi & Co Ltd, Bombay

SRI M. T. KANSE

Directorate General of Supplies & Disposals

SRI KARTIK PRASAD

Roads Wing, Ministry of Transport & Shipping

SRI S. L. KATHURIA (Alternate)

SRI S. R. KULKARNI

M. N. Dastur & Co (Private) Ltd, Calcutta

SRI M. A. MEHTA

Concrete Association of India, Bombay

SRI O. MUTHACHEN

Central Public Works Department

SUPERINTENDING ENGINEER,
2ND CIRCLE (Alternate)

SRI ERACH A. NADIRSHAH

Institution of Engineers (India), Calcutta

SRI K. K. NAMBIAR

In personal capacity ('Ramana Raya', 11 First Crescent
Park Road, Gandhinagar, Adyar, Madras)

(Continued on page 2)

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

IS : 6441 (Part I) - 1972

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
BRIG NARESH PRASAD	Engineer-in-Chief's Branch, Army Headquarters
COL J. M. TOLANI (<i>Alternate</i>)	
PROF G. S. RAMASWAMY	Structural Engineering Research Centre (CSIR Roorkee
DR N. S. BHAL (<i>Alternate</i>)	
DR A. V. R. RAO	National Buildings Organization, New Delhi
SHRI RAVINDER LAL (<i>Alternate</i>)	
SHRI G. S. M. RAO	Geological Survey of India, Nagpur
SHRI T. N. S. RAO	Gammon India Ltd, Bombay
SHRI S. R. PINHEIRO (<i>Alternate</i>)	
SECRETARY	Central Board of Irrigation & Power, New Delhi
SHRI R. P. SHARMA	Irrigation & Power Research Institute, Amritsar
SHRI MOHINDER SINGH (<i>Alternate</i>)	
SHRI G. B. SINGH	Hindustan Housing Factory Ltd, New Delhi
SHRI C. L. KASLIWAL (<i>Alternate</i>)	
SHRI J. S. SINGHOTA	Beas Designs Organization, Nangal Township
SHRI A. M. SINGAL (<i>Alternate</i>)	
SHRI K. A. SUBRAMANIAM	India Cements Ltd, Madras
SHRI T. S. RAMACHANDRAN (<i>Alternate</i>)	
SHRI L. SWAROOP	Dalmia Cement (Bharat) Ltd, New Delhi
SHRI A. V. RAMANA (<i>Alternate</i>)	
SHRI D. AJITHA SIMHA, Director (Civ Engg)	Director General, ISI (<i>Ex-officio Member</i>)

Secretary

SHRI Y. R. TANEJA
Deputy Director (Civ Engg), ISI

Precast Concrete Products Subcommittee, BDC 2 : 9

Convener

SHRI M. A. MEHTA Concrete Association of India, Bombay

Members

SHRI E. T. ANTIA (<i>Alternate to</i> Shri M. A. Mehta)	
SHRI V. A. ARTHANOOOR	Neyveli Lignite Corporation Ltd, Neyveli
SHRI T. RAMACHANDRAN (<i>Alternate</i>)	
SHRI H. B. CHATTERJEE	Hindustan Block Manufacturing Co Ltd, Calcutta
SHRI S. K. CHATTERJEE	Hindustan Housing Factory Ltd, New Delhi
DEPUTY DIRECTOR, STANDARDS (B & S)	Research, Designs & Standards Organization, Lucknow
ASSISTANT DIRECTOR, STAND- ARDS (M/C) (<i>Alternate</i>)	
DIRECTOR (CSMRS)	Central Water & Power Commission, New Delhi
DEPUTY DIRECTOR (CSMRS) (<i>Alternate</i>)	

(Continued on page 7)

Indian Standard

METHODS OF TEST FOR AUTOCLAVED CELLULAR CONCRETE PRODUCTS

PART I DETERMINATION OF UNIT WEIGHT OR BULK DENSITY AND MOISTURE CONTENT

0. FOREWORD

1 This Indian Standard (Part I) was adopted by the Indian Standards Institution on 21 February 1972, after the draft finalized by the Cement and Concrete Sectional Committee had been approved by the Civil Engineering Division Council.

2 Autoclaved cellular concrete is a class of material, which has been developed commercially abroad and is in the process of development in this country also. A series of Indian Standards on cellular concrete is being formulated so as to provide guidance in obtaining reliable products of autoclaved cellular concrete. The Sectional Committee has considered it desirable to issue a standard for the methods of test for autoclaved cellular concrete products for the guidance of manufacturers and users.

3 In the formulation of this standard due weightage has been given to international co-ordination among the standards and practices prevailing in different countries in addition to relating it to the practices in the field in this country.

4 For convenience of reference, 'Indian Standard methods of test for autoclaved cellular concrete products' has been grouped into the following nine parts:

- | | |
|----------|---|
| Part I | Determination of unit weight or bulk density and moisture content |
| Part II | Determination of drying shrinkage |
| Part III | Determination of thermal conductivity |
| Part IV | Corrosion protection of steel reinforcement in autoclaved cellular concrete |
| Part V | Determination of compressive strength |
| Part VI | Strength, deformation and cracking of flexural members subject to bending-short duration loading test |

Part VII Strength, deformation and cracking of flexural members subject to bending-sustained loading test

Part VIII Loading tests for flexural members in diagonal tension

Part IX Jointing of autoclaved cellular concrete elements

0.5 In reporting the result of a test made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS : 2-1960*.

1. SCOPE

1.1 This standard (Part I) covers the methods for determining the following:

- a) Unit weight or bulk density of autoclaved cellular concrete products, determined as the ratio between the weight of the specimen after drying at 105°C and volume of the specimen; and
- b) Moisture content of autoclaved cellular concrete products.

2. TEST SPECIMENS

2.1 Shape of Specimens — The bulk density and moisture content shall be determined on regularly shaped specimens (without reinforcement) with a minimum thickness of 50 mm. The two large surfaces of the specimen located opposite each other shall have a surface area of at least 20 000 mm² each and the length of the edge shall not be less than 100 mm.

NOTE 1 — A specimen of size 100 × 200 × 50 mm will meet the above requirements.

NOTE 2 — Whenever feasible, the specimens used for determination of bulk density and moisture content, and the specimen for determination of compressive strength should be cut from the same sample of cellular concrete product.

2.2 Location of Specimens — From each sample for which the density is to be determined, three test specimens shall be taken, and these shall form the test series. One specimen shall be taken from the upper third of the sample, one from the middle and one from the lower section. The position of the specimen is with reference to the direction of rise in aerated concrete mass during manufacture.

2.2.1 It is permissible to prepare the specimens from items which have previously been used for other tests provided the specimens are not cut within a distance of at least 15 cm from an area where visible damage or changes in the normal structure and appearance have occurred. The specimens shall not contain any reinforcement.

*Rules for rounding off numerical values (revised).

1.3 Preparation of Specimens — The specimens shall be cut by rotating carborundum blades or similar device. All surfaces shall be clean cut and plane. The largest surface shall not deviate from planeness by more than 0.1 mm, if measured diagonally with a straight-edge.

3. APPARATUS

3.1 Straight-Edge — approximately 500 mm long.

3.2 Calliper — allows readings to an accuracy of 0.1 mm.

3.3 Drying Oven — for a temperature of $105 \pm 5^\circ\text{C}$.

3.4 Balance — with a weighing accuracy of 0.5 g.

4. PROCEDURE

4.1 Bulk Density

4.1.1 Measurement of Specimens — Length, width and thickness shall be measured before drying at 105°C with an accuracy of 0.1 mm using a suitable calliper. These measurements shall permit the determination of the volume V of the specimen with an error not exceeding one percent.

4.1.2 Drying of Specimens — After measuring, the specimens shall be placed in a drying oven at $105 \pm 5^\circ\text{C}$ until all moisture has been removed and constant weight is obtained. Immediately after removing from the drying oven, the specimens shall be weighed (*see Note*). The weighing error shall not exceed 0.1 percent of the weight of the specimen. The weight W of the specimen shall be considered constant if the weight after four hours further drying has not changed more than 0.2 percent.

NOTE — To facilitate handling, the specimen after removal from the oven, may be cooled to room temperature in a suitable desiccator and weighed immediately.

4.2 Moisture Content

4.2.1 Weighing of Specimens — The specimen as in 4.1.1 (or immediately after loading, in case the moisture content is to be determined for compressive strength specimens (*see 1.1 and 2.1*), shall be weighed. The weighing error shall not exceed 0.1 percent. This weight shall be designated W_1 .

4.2.2 After weighing, the specimen shall be dried out at $105 \pm 5^\circ\text{C}$ as in 4.1.2 until constant weight is obtained within a duration of four hours.

Immediately after removing from the drying oven, the specimen shall be weighed (if necessary by cooling to room temperature in a suitable desiccator), and weight W obtained as in 4.1.2.

5. CALCULATIONS

5.1 The bulk density γ in g/cm³ shall be calculated as follows:

$$\gamma = \frac{W}{V} \text{ (g/cm}^3\text{)}$$

where

W = dry weight of the specimen in g, and

V = volume in cm³.

5.1.1 Bulk density of the individual specimens shall be calculated and reported within the three decimal places, the mean value of the three specimens shall be within two decimal places.

5.2 Moisture content F in weight, percent of the dry material, shall be determined as follows:

$$F = \frac{W_1 - W}{W} \times 100 \text{ (percent)}$$

where

W_1 = sampled weight of the specimen in g, and

W = dry weight of the specimen in g.

5.2.1 Moisture content of individual specimen shall be stated in whole percent, and the mean value of three specimens shall also be stated in whole percent.

6. REPORT

6.1 The report shall include the following:

- a) Code designation;
- b) Identification of product;
- c) Date of manufacture;
- d) Place, method and time of sampling;
- e) Bulk density of each specimen and mean value of test series; and
- f) Moisture content of each specimen and mean value of test series.

*Continued from page 2)***Members**

SHRI K. C. GHOSAL
 SHRI A. K. BISWAS (*Alternate*)
 SHRI M. K. GUPTA
 SHRI B. D. JAYARAMAN
 SHRI B. K. JINDAL

DR S. S. REHSI (*Alternate*)

SHRI L. C. LAI
 SHRI G. C. MATHUR

ASSISTANT DIRECTOR (*DESIGNS*) (*Alternate*)

SHRI S. NAHARAY

SHRI A. RAMAKRISHNA (*Alternate*)

SHRI K. K. NAMBIAR

SHRI RADHEY SHIAM

SHRI B. G. SHIRKE

SHRI R. A. DESHMUKH (*Alternate*)

SHRI C. N. SRINIVASAN

SHRI C. N. RAGHAVENDRAN (*Alternate*)

SURVEYOR OF WORKS (I)

DR H. C. VISVESVARAYA

Representing

Alokudyog Services Ltd, New Delhi

Himalayan Tiles & Marble Pvt Ltd, Bombay

State Housing Board, Madras

Central Building Research Institute (CSIR),
 Roorkee

In personal capacity (*B/17, West End, New Delhi 23*)

National Buildings Organization, New Delhi

Engineering Construction Corporation Ltd, Madras

In personal capacity (' *Ramanalaya* ', *11 First
 Crescent Park Road, Gandhinagar, Adyar, Madras*)

Engineer-in-Chief's Branch, Army Headquarters

B. G. Shirke & Co, Poona

C. R. Narayana Rao, Madras

Central Public Works Department

Cement Research Institute of India, New Delhi

BUREAU OF INDIAN STANDARDS

Headquarters :

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones : 331 01 31

Telegrams : Manaksans

331 13 75

(Common to all Office

Regional Offices :

Telephc

Central	: Manak Bhavan, 9, Bahadur Shah Zafar Marg NEW DELHI 110002	{ 331 01 331 13
* Eastern	: 1/14 C.I.T. Scheme VII M. V.I.P. Road, Maniktola, CALCUTTA 700054	37 86
Northern	: SCO 445-446, Sector 35-C, CHANDIGARH 160036	2 18
Southern	: C.I.T. Campus, IV Cross Road, MADRAS 600113	41 29
† Western	: Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	6 32 92

Branch Offices :

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	2 63
‡ Peeriya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058	39 49
Gangotri Complex, 5th Floor, Bhadbhada Road, T.T. Nagar, BHOPAL 462003	55 40
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	5 36
Kalai Kathir Building, 6/48-A Avanasi Road, COIMBATORE 641037	2 67
Quality Marking Centre, N.H. IV, N.I.T., FARIDABAD 121001	—
Savitri Complex, 116 G. T. Road, GHAZIABAD 201001	8-71 19
53/5 Ward No. 29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	3 31
5-8-56C L. N. Gupta Marg, (Nampally Station Road) HYDERABAD 500001	23 10
R14 Yudhister Marg, C Scheme, JAIPUR 302005	6 34
117/418 B Sarvodaya Nagar, KANPUR 208005	21 68
Plot No. A-9, House No. 561/63, Sindhu Nagar, Kanpur Road, LUCKNOW 226005	5 55
Palliputra Industrial Estate, PATNA 800013	6 23
District Industries Centre Complex, Bagh-e-Ali Maidan, SRINAGAR 190011	—
T. C. No. 14/1421, University P. O., Palayam, THIRUVANANTHAPURAM 695034	6 21
<i>Inspection Offices (With Sale Point) :</i>	
Pushpanjali, First Floor, 205-A West High Court Road, Shankar Nagar Square, NAGPUR 440010	52 51
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	5 24
*Sales Office Calcutta is at 5 Chowringhee Approach, P. O. Princep Street, CALCUTTA	27 68
† Sales Office is at Novelty Chambers, Grant Road, BOMBAY	89 65
‡ Sales Office is at Unity Building, Narasimharaja Square, BANGALORE	22 35